


Mini Recovery Unit VRR24L

Making Your Job More Enjoyable !



Light • Faster

One Key Operation

- Easy to use

Twin Cylinder

- Faster recovery

Oil-free Compressor

- Suitable for all commonly used refrigerants

Self-purge Function

- Prevent mixing of various refrigerants

High Pressure Protection

- Added safety

Model	VRR24L			VRR24L-OS		
Refrigerant	Categories III : R12, R134a, R401C, R500 Categories IV : R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509 Categories V : R402A, R404A, R407A, R407B, R410A, R507					
Power Supply	220-240V~/50-60Hz	115V~/60Hz	220V-240V~/50-60Hz	115V~/60Hz		
Motor	1 HP	1 HP	1 HP	1 HP		
Motor Speed	1450rpm/1750rpm	1750rpm	1450rpm/1750rpm	1750rpm		
Maximal Current Draw	5 A	10 A	5 A	10 A		
Compressor	Oil-less, Air-cooled, Piston style					
Automatic Safety Shut-Off	38.5bar/3850kPa(558psi)					
Recovery Rate (kg/min)	Categories III	Categories IV	Categories V	Categories III	Categories IV	Categories V
	Vapor	0.40	0.50	0.50	0.40	0.50
	Liquid	3.00	3.50	3.50	3.00	3.50
	Push/pull	7.50	8.50	9.50	7.50	9.50
Operating Temperature	0 °C-40 °C					
Dimensions	450×250×355 mm					
Weight	13.5 kg			14.7 kg		